

---

# A Unified Analytical Framework for Stability and Energy Analysis of Multi-Term Fractional Dynamical Systems

**Original Research Article**

*Received: XX December 20XX  
Accepted: XX December 20XX  
Online Ready: XX December 20XX*

## Abstract

This work develops a unified fractional calculus framework for modeling memory dependent behavior in viscoelastic materials, electrical circuits, and control systems. The study emphasizes rigorous mathematical analysis of multi-term fractional operators and establishes well posedness and dissipativity properties for heterogeneous fractional viscoelastic models through a novel energy functional approach. For fractional order circuit representations, a bounded input bounded output stability result is derived, ensuring the physical realizability of nonlocal impedance elements. In the control domain, a practical stability theorem is proven for adaptive fractional PID controllers, providing guaranteed bounded tracking performance under memory driven adaptation. These results demonstrate that fractional operators not only enhance modeling flexibility but also preserve fundamental stability and energy principles, offering a mathematically consistent foundation for advanced engineering system design.

*Keywords: Fractional calculus; multi-term fractional operators; viscoelastic systems; fractional dynamical systems; stability analysis; dissipative systems; fractional order control.*

2010 Mathematics Subject Classification: 26A33; 34A08; 74D05; 93C15; 47G20

## 1 Introduction

Classical calculus has long provided the foundation for modeling dynamical systems in science and engineering. Its integer-order derivatives describe local rates of change and have proven effective for a wide range of phenomena. However, many real processes exhibit hereditary and nonlocal effects that cannot be adequately captured using purely local differential operators. Materials with internal memory, systems with long relaxation times, and processes influenced by historical states require mathematical tools that extend beyond classical formulations.

Fractional calculus offers such a framework by allowing differentiation and integration of non-integer order [5, 12, 13, 14]. Fractional operators inherently incorporate memory, as their definitions involve integral kernels spanning the past history of the state variable. This feature makes them particularly suitable for modeling viscoelastic media, anomalous transport, dielectric relaxation, and

---

---

memory dependent control mechanisms [12, 13]. Unlike integer order models, fractional formulations provide a continuous transition between purely elastic and purely viscous responses, enabling more realistic descriptions of complex materials.

Over the past decades, fractional calculus has found increasing use in engineering sciences. In viscoelasticity, fractional stress–strain relations have been shown to represent power law relaxation and creep behaviors with a small number of parameters. In circuit theory, fractional impedance elements generalize capacitive and inductive behavior through frequency dependent memory effects. In control engineering, fractional order controllers extend the classical PID structure, introducing additional degrees of freedom that improve robustness and transient performance [2, 4, 9, 10, 11, 15]. Despite these advances, rigorous mathematical analysis often lags behind modeling practice [1, 3, 7]. Many fractional models are introduced phenomenologically, while their stability, boundedness, and energy properties are not thoroughly established.

The present work addresses this gap by developing a unified analytical framework for a class of multi-term fractional systems arising in mechanics, electrical networks, and control theory [7, 19]. Rather than emphasizing numerical illustrations, the focus is placed on structural properties of fractional operators and their implications for system behavior.

First, a heterogeneous fractional viscoelastic model is analyzed. By constructing an appropriate energy functional, we establish well posedness and prove that the system is intrinsically dissipative. This result provides a rigorous mathematical explanation for irreversible energy loss in materials governed by fractional stress laws.

Second, a fractional circuit model involving multi-term integral operators is studied from an operator theoretic perspective. A bounded-input bounded-output stability property is derived, ensuring that memory dependent impedance elements do not produce unphysical growth in voltage response on finite time intervals.

Third, we investigate an adaptive fractional PID control structure. By treating the fractional terms as bounded memory perturbations of a stabilizing linear controller, a practical stability result is obtained that guarantees bounded tracking performance under time varying fractional orders.

These results demonstrate that fractional models can be analyzed within a rigorous mathematical framework while preserving their ability to represent nonlocal and memory dependent dynamics. The paper therefore contributes to the theoretical foundations of fractional engineering systems, providing analytical tools that complement existing modeling approaches.

## 2 Viscoelastic Materials: Fractional Order Modeling

Viscoelastic materials, such as polymers, exhibit both elastic and viscous properties, with stress strain relationships that depend on the history of deformation. The fractional order model  $\sigma(t) = ED^\alpha \varepsilon(t)$ , where  $D^\alpha$  is the fractional derivative of order  $0 < \alpha < 1$ ,  $E$  is a material constant,  $\sigma(t)$  is stress, and  $\varepsilon(t)$  is strain, effectively captures this memory dependent behavior.

### 2.1 Fractional Viscoelastic Model

We propose a generalized fractional viscoelastic model that incorporates multiple fractional orders to account for the properties of heterogeneous material:

$$\sigma(t) = E_1 D^{\alpha_1} \varepsilon(t) + E_2 D^{\alpha_2} \varepsilon(t), \quad 0 < \alpha_1, \alpha_2 < 1, \quad (2.1)$$

where  $E_1, E_2$  are material constants, and  $\alpha_1, \alpha_2$  represent distinct fractional orders reflecting different relaxation mechanisms. Such multi-term fractional viscoelastic models have been widely used to describe heterogeneous relaxation mechanisms [5, 7, 12].

The *heterogeneous fractional viscoelasticity model* is defined by the stress strain relationship given in (2.1), where the fractional derivatives  $D^{\alpha_1}$  and  $D^{\alpha_2}$  are of Caputo type, ensuring compatibility

with the physical initial conditions [12, 14]. Existence and uniqueness results for linear and nonlinear fractional differential equations provide the theoretical foundation for the well posedness of such models [1, 14].

**Theorem 2.1** (Well posedness and dissipativity of the heterogeneous fractional viscoelastic model). *Consider the stress–strain relation*

$$\sigma(t) = E_1 {}^C D_t^{\alpha_1} \varepsilon(t) + E_2 {}^C D_t^{\alpha_2} \varepsilon(t), \quad 0 < \alpha_1 < \alpha_2 < 1,$$

where  ${}^C D_t^\alpha$  denotes the Caputo fractional derivative and  $E_1, E_2 > 0$ . Assume the strain satisfies the evolution equation

$$\rho \ddot{\varepsilon}(t) + \gamma \dot{\varepsilon}(t) + \sigma(t) = f(t),$$

with  $\rho, \gamma > 0$  and  $f \in L^2(0, T)$ .

Then for initial data  $\varepsilon(0) = \varepsilon_0$  and  $\dot{\varepsilon}(0) = v_0$ , there exists a unique solution

$$\varepsilon \in C^1([0, T]).$$

Moreover, the system is dissipative in the sense that the energy functional

$$\mathcal{E}(t) = \frac{\rho}{2} |\dot{\varepsilon}(t)|^2 + \frac{E_1}{2} I^{1-\alpha_1}(\dot{\varepsilon}^2)(t) + \frac{E_2}{2} I^{1-\alpha_2}(\dot{\varepsilon}^2)(t)$$

satisfies

$$\mathcal{E}(t) + \gamma \int_0^t |\dot{\varepsilon}(\tau)|^2 d\tau \leq \mathcal{E}(0) + \int_0^t f(\tau) \dot{\varepsilon}(\tau) d\tau.$$

In particular, if  $f = 0$ , then  $\mathcal{E}(t)$  is non increasing on  $[0, T]$ .

*Proof.* We rewrite the governing equation as

$$\rho \ddot{\varepsilon}(t) + \gamma \dot{\varepsilon}(t) + E_1 {}^C D_t^{\alpha_1} \varepsilon(t) + E_2 {}^C D_t^{\alpha_2} \varepsilon(t) = f(t).$$

**Step 1: Existence and uniqueness.** Using the definition of the Caputo derivative [1, 7, 12],

$${}^C D_t^\alpha \varepsilon(t) = I^{1-\alpha} \dot{\varepsilon}(t),$$

the equation can be expressed as a Volterra integro differential equation:

$$\rho \ddot{\varepsilon}(t) + \gamma \dot{\varepsilon}(t) + E_1 I^{1-\alpha_1} \dot{\varepsilon}(t) + E_2 I^{1-\alpha_2} \dot{\varepsilon}(t) = f(t).$$

The fractional integral operators are bounded linear operators from  $L^2(0, T)$  into  $L^2(0, T)$ . Hence the equation is equivalent to a second order equation with memory kernel of convolution type. The Caputo derivatives can be written as convolution operators

$${}^C D_t^{\alpha_i} \varepsilon(t) = \frac{1}{\Gamma(1-\alpha_i)} \int_0^t (t-\tau)^{-\alpha_i} \dot{\varepsilon}(\tau) d\tau, \quad i = 1, 2.$$

Since the kernels  $(t-\tau)^{-\alpha_i}$  are weakly singular and integrable on  $(0, t)$  [6, 8], for every  $t > 0$  when  $0 < \alpha_i < 1$ , the governing equation can be rewritten as a linear Volterra integro differential equation with weakly singular memory kernels. Such systems are known to admit unique solutions in  $C^1([0, T])$  by classical resolvent kernel theory for Volterra equations.

**Step 2: Energy identity.** Multiply the governing equation by  $\dot{\varepsilon}(t)$  and integrate from 0 to  $t$ :

$$\rho \int_0^t \ddot{\varepsilon} \dot{\varepsilon} d\tau + \gamma \int_0^t |\dot{\varepsilon}|^2 d\tau + E_1 \int_0^t (I^{1-\alpha_1} \dot{\varepsilon}) \dot{\varepsilon} d\tau + E_2 \int_0^t (I^{1-\alpha_2} \dot{\varepsilon}) \dot{\varepsilon} d\tau = \int_0^t f(\tau) \dot{\varepsilon}(\tau) d\tau.$$

The first term yields

$$\rho \int_0^t \ddot{\varepsilon} \dot{\varepsilon} d\tau = \frac{\rho}{2} |\dot{\varepsilon}(t)|^2 - \frac{\rho}{2} |\dot{\varepsilon}(0)|^2.$$

---

Using the positivity of fractional integrals,

$$\int_0^t (I^{1-\alpha} \dot{\varepsilon}) \dot{\varepsilon} d\tau = \frac{1}{2} I^{1-\alpha} (\dot{\varepsilon}^2)(t),$$

we obtain

$$\mathcal{E}(t) - \mathcal{E}(0) + \gamma \int_0^t |\dot{\varepsilon}|^2 d\tau = \int_0^t f(\tau) \dot{\varepsilon}(\tau) d\tau,$$

where

$$\mathcal{E}(t) = \frac{\rho}{2} |\dot{\varepsilon}(t)|^2 + \frac{E_1}{2} I^{1-\alpha_1} (\dot{\varepsilon}^2)(t) + \frac{E_2}{2} I^{1-\alpha_2} (\dot{\varepsilon}^2)(t).$$

**Step 3: Dissipativity.** If  $f = 0$ , the right hand side vanishes and

$$\mathcal{E}(t) + \gamma \int_0^t |\dot{\varepsilon}|^2 d\tau = \mathcal{E}(0),$$

which shows  $\mathcal{E}(t)$  is non increasing. The construction of such fractional energy functionals is consistent with modern stability analysis for fractional systems [3, 6, 10]. Hence the system is dissipative.  $\square$

## 2.2 Physical Interpretation of the Dissipative Behavior

The energy inequality established in Theorem 2.1 provides a direct physical interpretation of the heterogeneous fractional viscoelastic model. The presence of Caputo fractional derivatives introduces memory dependent damping, which naturally leads to irreversible energy loss over time.

In classical viscoelasticity, damping is typically modeled using integer order derivatives [5, 12], resulting in exponential decay of oscillations. In contrast, the fractional operators in the present model produce a history dependent response, where the rate of energy dissipation is governed by the fractional orders  $\alpha_1$  and  $\alpha_2$ . Smaller fractional orders correspond to stronger memory fading and enhanced damping [6, 7], while larger orders retain elastic memory for longer durations.

Theorem 2.1 rigorously confirms that, in the absence of external forcing, the total system energy is non increasing. This establishes the model as intrinsically dissipative and consistent with the thermodynamic behavior of real viscoelastic materials. Consequently, the fractional parameters serve as tunable quantities that regulate the balance between energy storage and energy dissipation in complex polymeric structures.

## 3 Fractional Order Electrical Circuits

Fractional order circuits incorporate elements like capacitors and inductors with non-integer order impedance, such as  $Z(s) = \frac{1}{C_s^\alpha}$ , where  $0 < \alpha < 1$ . These models account for frequency dependent losses in real world components.

### 3.1 Fractional Circuit Model

We introduce a fractional order RC circuit with a composite impedance:

$$Z(s) = R + \frac{1}{C_1 s^{\alpha_1} + C_2 s^{\alpha_2}}, \quad 0 < \alpha_1, \alpha_2 < 1, \quad (3.1)$$

where  $R$  is resistance, and  $C_1, C_2$  are fractional capacitance with orders  $\alpha_1, \alpha_2$ . Fractional impedance models of this type are commonly used to represent dielectric and electrochemical memory effects [12, 13].

---

**Theorem 3.1** (BIBO stability of a multi-term fractional RC circuit). *Consider the fractional circuit governed by [3, 18],*

$$V(t) = RI(t) + \frac{1}{C_1} I^{\alpha_1} I(t) + \frac{1}{C_2} I^{\alpha_2} I(t), \quad 0 < \alpha_1 < \alpha_2 < 1,$$

where  $I^\alpha$  denotes the Riemann–Liouville fractional integral.

If the input current satisfies  $I \in L^\infty(0, \infty)$ , then the output voltage  $V(t)$  is bounded on every finite interval  $[0, T]$ . More precisely,

$$\|V\|_{L^\infty(0, T)} \leq R\|I\|_{L^\infty} + \frac{T^{\alpha_1}}{C_1\Gamma(1 + \alpha_1)}\|I\|_{L^\infty} + \frac{T^{\alpha_2}}{C_2\Gamma(1 + \alpha_2)}\|I\|_{L^\infty}.$$

Furthermore, the system defines a causal bounded linear operator from  $L^\infty$  to  $C([0, T])$ .

*Proof.* Assume  $I(t)$  is bounded:  $|I(t)| \leq M$  for all  $t \geq 0$ .

The fractional integrals satisfy [12],

$$|I^\alpha I(t)| = \left| \frac{1}{\Gamma(\alpha)} \int_0^t (t - \tau)^{\alpha-1} I(\tau) d\tau \right| \leq \frac{M}{\Gamma(\alpha)} \int_0^t (t - \tau)^{\alpha-1} d\tau = \frac{Mt^\alpha}{\Gamma(1 + \alpha)}.$$

Thus,

$$|V(t)| \leq RM + \frac{Mt^{\alpha_1}}{C_1\Gamma(1 + \alpha_1)} + \frac{Mt^{\alpha_2}}{C_2\Gamma(1 + \alpha_2)}.$$

For any finite interval  $[0, T]$ ,

$$\sup_{0 \leq t \leq T} |V(t)| \leq M \left( R + \frac{T^{\alpha_1}}{C_1\Gamma(1 + \alpha_1)} + \frac{T^{\alpha_2}}{C_2\Gamma(1 + \alpha_2)} \right),$$

which proves boundedness.

Linearity and causality follow directly from the convolution form of the fractional integrals. Hence the system is BIBO stable on finite horizons.  $\square$

**Remark:** Although boundedness of fractional integrals is a classical analytical property, its formulation in Theorem 3.1 has an important structural interpretation. The multi-term fractional impedance relation can be viewed as a convolution operator [6, 8] with weakly singular memory kernels acting on the input current. The theorem therefore ensures that such fractional circuit elements define bounded, causal operators on signal spaces over finite time intervals. This guarantees that memory dependent impedance models remain physically realizable and do not introduce artificial energy growth due to nonlocal effects.

## 3.2 Interpretation of the Fractional Circuit Model

The boundedness result established in Theorem 3.1 provides a theoretical foundation for fractional order circuit elements. Unlike ideal capacitors, fractional capacitors exhibit memory dependent impedance that evolves with time. The theorem guarantees that, for bounded current inputs, the voltage response remains bounded on finite time intervals, ensuring physical realizability and preventing unbounded energy accumulation.

This property confirms that multi-term fractional impedance models are mathematically well posed and suitable for describing lossy dielectric materials and electrochemical systems where nonlocal charge dynamics play a significant role.

## 4 Fractional Order Control Systems

Fractional order PID controllers, defined as [13, 18]:

$$u(t) = K_p e(t) + K_i D^{-\lambda} e(t) + K_d D^\mu e(t), \quad 0 < \lambda, \mu < 1,$$

offer enhanced flexibility in controlling complex systems. We propose a novel adaptive fractional PID controller with dynamic order adjustment.

### 4.1 Adaptive Fractional PID Controller

The controller adjusts  $\lambda$  and  $\mu$  based on the error dynamics:

$$\lambda(t) = \lambda_0 + k_1 |e(t)|, \quad \mu(t) = \mu_0 + k_2 |e(t)|, \quad (4.1)$$

where  $\lambda_0, \mu_0$  are nominal orders, and  $k_1, k_2$  are tuning parameters. Adaptive adjustment of fractional orders has been explored as a mechanism for improving robustness in memory dependent controllers [2, 6, 9, 11, 17].

**Theorem 4.1** (Practical stability of an adaptive fractional PID controller). *Consider the linear system [16, 17, 19],*

$$\dot{x}(t) = Ax(t) + Bu(t), \quad e(t) = r(t) - x(t),$$

and the adaptive fractional PID controller

$$u(t) = K_p e(t) + K_i I^{\lambda(t)} e(t) + K_d {}^C D_t^{\mu(t)} e(t),$$

where  $I^{\lambda(t)}$  denotes the Riemann–Liouville fractional integral of order  $\lambda(t)$  and

$$\lambda(t) = \lambda_0 + k_1 |e(t)|, \quad \mu(t) = \mu_0 + k_2 |e(t)|,$$

with  $0 < \lambda_0, \mu_0 < 1$  and  $k_1, k_2 > 0$ .

Assume  $(A, B)$  is controllable, the reference  $r(t)$  is bounded, and full state feedback is available. Then there exist controller gains  $K_p, K_i, K_d$  such that the closed loop error satisfies

$$\limsup_{t \rightarrow \infty} |e(t)| \leq \delta,$$

for some  $\delta > 0$  depending on  $k_1, k_2$ . Hence the system is practically stable and achieves bounded tracking with memory dependent adaptation.

*Proof.* Let the tracking error be  $e(t) = r(t) - x(t)$  with bounded reference  $r(t)$ . For linear systems with continuous inputs, the state and hence the error remain continuously differentiable on finite intervals; therefore we assume

$$e \in C^1([0, T]).$$

The closed-loop system can be written as

$$\dot{x}(t) = Ax(t) + B[K_p e(t) + K_i I^{\lambda(t)} e(t) + K_d {}^C D_t^{\mu(t)} e(t)].$$

**Step 1: Boundedness of adaptive orders.** Since  $e(t)$  is continuous and bounded on finite intervals,

$$\lambda(t) = \lambda_0 + k_1 |e(t)|, \quad \mu(t) = \mu_0 + k_2 |e(t)|$$

remain in a compact subset of  $(0, 1)$ .

**Step 2: Bounded control signal.** Since fractional integral and Caputo derivative operators of order less than one map  $C^1([0, T])$  functions into bounded functions on  $[0, T]$  [3, 8] (by continuity of weakly singular convolution operators), there exist constants  $C_1, C_2 > 0$  such that for each  $t \in [0, T]$ ,

$$|I^{\lambda(t)} e(t)| \leq C_1 \sup_{0 \leq \tau \leq t} |e(\tau)|, \quad |{}^C D_t^{\mu(t)} e(t)| \leq C_2 \sup_{0 \leq \tau \leq t} |e(\tau)|.$$

Hence, for some constant  $C_3 > 0$ ,

$$|u(t)| \leq C_3 \sup_{0 \leq \tau \leq t} |e(\tau)|.$$

**Step 3: Practical stability.** Because  $(A, B)$  is controllable, choose  $K_p$  such that  $A - BK_p$  is Hurwitz. Define

$$\Delta(t) = K_i I^{\lambda(t)} e(t) + K_d {}^C D_t^{\mu(t)} e(t).$$

Then the closed-loop dynamics can be written as

$$\dot{x}(t) = (A - BK_p)x(t) + B\Delta(t),$$

where  $|\Delta(t)| \leq C_4 \sup_{0 \leq \tau \leq t} |e(\tau)|$  for some constant  $C_4 > 0$ .

Taking norms and using the bound on  $\Delta(t)$  gives

$$|x(t)| \leq M e^{-\eta t} |x(0)| + M \int_0^t e^{-\eta(t-s)} |\Delta(s)| ds,$$

for some  $M, \eta > 0$ . Using the bound on  $\Delta(t)$  and the boundedness of  $r(t)$ , the integral term can be estimated by a constant depending on  $k_1, k_2$ . Applying the variation of constants formula and estimating the perturbation term using Grönwall's inequality yields [8, 16],

$$|e(t)| \leq \beta e^{-\eta t} |x(0)| + \delta,$$

where  $\delta$  depends on  $k_1, k_2$ . Therefore,

$$\limsup_{t \rightarrow \infty} |e(t)| \leq \delta,$$

which proves practical stability. □

*Remark 4.1.* The use of practical stability in Theorem 4.1 is natural in the context of fractional and adaptive control systems. Fractional operators introduce long memory effects, while the adaptive laws make the controller parameters time varying. These features generally prevent strict asymptotic convergence to zero from being guaranteed under realistic assumptions. Instead, ensuring that the tracking error remains confined within a small neighborhood of the origin provides a more appropriate and physically meaningful stability notion. The result therefore reflects the inherent nonlocal dynamics of fractional systems while still guaranteeing reliable bounded performance.

## 4.2 Control Interpretation of the Practical Stability Result

Theorem 4.1 establishes practical stability for linear systems controlled by an adaptive fractional order PID structure. In the context of motor speed regulation, the state vector represents the electromechanical dynamics of the motor, while the control input corresponds to the applied voltage or torque signal.

The adaptive fractional orders  $\lambda(t)$  and  $\mu(t)$  introduce memory dependent correction terms [13, 6], that adjust according to the tracking error. This mechanism enhances transient performance by allowing stronger corrective action during large deviations and smoother behavior near steady state.

The theorem guarantees that, provided the plant is controllable and the reference signal is bounded, the tracking error remains confined within a small neighborhood of zero. This ensures reliable speed regulation without the risk of instability caused by parameter variation or external disturbances.

Thus, the adaptive fractional controller offers a mathematically justified framework for improving robustness and flexibility in motor control applications, while maintaining guaranteed bounded performance.

---

## 5 Conclusion and Future Scope

In this work, we have developed a unified analytical framework for multi-term fractional dynamical systems, aimed at providing a rigorous and structurally consistent treatment of stability and energy behavior across multiple engineering domains. The main contribution lies in bridging viscoelasticity, fractional electrical circuits, and adaptive control systems within a common operator-theoretic setting governed by nonlocal fractional dynamics.

From a mathematical perspective, Theorem 2.1 establishes well-posedness and dissipativity of heterogeneous fractional viscoelastic models through the construction of an appropriate fractional energy functional. This result provides a generalized mechanism for characterizing memory-induced energy decay beyond classical integer-order damping. Theorem 3.1 demonstrates bounded-input bounded-output stability for multi-term fractional circuit models, ensuring that convolution-type fractional impedance operators define bounded and causal mappings on signal spaces. Furthermore, Theorem 4.1 introduces a practical stability result for adaptive fractional PID controllers, showing that memory-dependent control laws with variable fractional orders yield guaranteed bounded tracking performance under suitable controllability conditions.

Collectively, these results show that multi-term fractional operators admit a unified analytical interpretation in terms of dissipativity, boundedness, and stability, thereby extending classical system theory to nonlocal and memory-dependent settings. In particular, the formulation of fractional energy functionals and operator bounds provides a systematic framework that avoids purely phenomenological modeling and instead emphasizes mathematically verifiable system properties.

Despite these contributions, certain limitations remain. The present analysis is largely confined to linear or weakly nonlinear systems and relies on finite-time boundedness arguments. The assumptions on smoothness, bounded inputs, and controllability restrict the direct applicability to more complex or uncertain environments. In addition, the absence of detailed numerical simulations and experimental validation limits the immediate engineering implementation of the proposed framework.

Future research will focus on extending the present theory in several directions. A natural extension is the study of nonlinear multi-term fractional systems, where energy methods must be adapted to account for strong nonlinear interactions. Another promising direction involves distributed parameter systems and fractional partial differential equations, where spatial memory effects play a crucial role. The incorporation of variable-order and state-dependent fractional operators also represents an important step toward modeling adaptive and evolving systems with dynamic memory structures.

Moreover, the integration of the proposed analytical framework with high-accuracy numerical schemes and computational simulations will be essential for validating theoretical predictions and enabling practical applications. Such developments are expected to significantly enhance the applicability of fractional models in advanced materials, electrochemical systems, and robust adaptive control, thereby strengthening the connection between rigorous mathematical analysis and real-world engineering systems.

## References

- [1] Menaria A. K. Existence and uniqueness of linear and non-linear fractional differential equations. *Journal of Interdisciplinary Mathematics*, 27(8):1915–1921, 2024.
- [2] N. Aguila-Camacho and J. Gallegos. Error-based switched fractional order model reference adaptive control for mimo linear time invariant systems. *Fractal and Fractional*, 2024.
- [3] D. Ahmad, Ravi P. Agarwal, and G. Rahman. Formulation, solution's existence, and stability analysis for multi-term system of fractional-order differential equations. *Symmetry*, 14:1342, 2022.

- 
- [4] Saim Ahmed and A. Azar. Adaptive fractional tracking control of robotic manipulator using fixed-time method. *Complex Intelligent Systems*, 10:369–382, 2023.
- [5] Ronald L. Bagley and Peter J. Torvik. A theoretical basis for the application of fractional calculus to viscoelasticity. *Journal of Rheology*, 27(3):201–210, 1983.
- [6] Dumitru Baleanu, S. Arshad, A. Jajarmi, W. Shokat, F. Ghassabzade, and M. Wali. Dynamical behaviours and stability analysis of a generalized fractional model with a real case study. *Journal of Advanced Research*, 48:157–173, 2022.
- [7] O. Brandibur and E. Kaslik. Stability analysis of multi-term fractional-differential equations with three fractional derivatives. *Journal of Mathematical Analysis and Applications*, 2020.
- [8] G. Datseris, K. Rossi, and A. Wagemakers. Framework for global stability analysis of dynamical systems. *Chaos*, 33(7), 2023.
- [9] Lusong Ding and Weiwei Sun. Neuro-adaptive finite-time control of fractional-order nonlinear systems with multiple objective constraints. *Mathematical Modelling and Control*, 2023.
- [10] M. Lavanya, B. Sundara Vadivoo, I. Alraddadi, D. Pamucar, O. Oqilat, and Hijaz Ahmad. Stochastic stability and controllability analysis of impulsive multi-term fractional differential system. *European Journal of Pure and Applied Mathematics*, 2025.
- [11] Boutheina Maalej, Ahmed Chemori, Rim Jallouli-Khlif, and Nabil Derbel. A new fractional-order  $L_1$  adaptive feedback control of dynamical systems: Design, stability analysis, and application. *Asian Journal of Control*, 2025.
- [12] Francesco Mainardi. *Fractional Calculus and Waves in Linear Viscoelasticity: An Introduction to Mathematical Models*. Imperial College Press, 2010.
- [13] Concepción A. Monje, YangQuan Chen, Blas M. Vinagre, Dingyu Xue, and Vicente Feliu-Batlle. *Fractional-Order Systems and Controls: Fundamentals and Applications*. Springer, 2010.
- [14] H. Nagar and A. K. Menaria. Applications of fractional hamilton equations within caputo derivatives. *Journal of Computer and Mathematical Sciences Vol*, 3(3):248–421, 2012.
- [15] Maryam Najari and Saeed Balochian. Adaptive predictive control of fractional order chaotic systems. *ELECTRICA*, 2024.
- [16] R. Orim, A. Panle, M. Ineh, A. Maharaj, and O. Narain. Strict uniform stability analysis in terms of two measures of caputo fractional dynamic systems on time scale. *Advances in Fixed Point Theory*, 2025.
- [17] B. Pervaiz, A. Zada, S. Etemad, and S. Rezapour. An analysis on the controllability and stability to some fractional delay dynamical systems on time scales with impulsive effects. *Advances in Difference Equations*, 2021:1–36, 2021.
- [18] Y. Qin, A. Khan, I. Ali, A. Qurashi, H. Khan, R. Shah, and D. Baleanu. An efficient analytical approach for the solution of certain fractional-order dynamical systems. *Energies*, 13:2725, 2020.
- [19] K. M. Saad, M. S. Abdo, and W. M. Hamanah. Existence and controllability analysis of multi-term fractional coupled systems with generalized  $[\psi, w]$ -caputo-fabrizio operators. *Scientific Reports*, 15:34434, 2025.

---

©Copyright (2025): Author(s). The licensee is the journal publisher. This is an Open Access article distributed under the terms of the Creative Commons Attribution License <http://creativecommons.org/licenses/by/4.0>, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.